# WINEMASTER le temps d'être différent

### THE MOST BEAUTIFUL WINDOW SHOWCASE

In order to meet the building requirements for glassed-in spaces, WineMaster<sup>®</sup> is launching a new line of wine cellar air conditioners: SPLIT SP40s. Whether you are a passionate connoisseur or a restaurant business professional, your wine collection deserves the prettiest window showcases for the enjoyment of all.



Air-conditioning up to 40m<sup>3</sup>





Respectful of the environment

Ideal climate conditions for the preservation of your wine

# WINE SP40 CA PRO

### THE SPLIT UNITS






# WINE SP40 CA PRO


- $\blacksquare$  Keeps cellars at a constant temperature of between 8 and 18 °C \*
- Humidity control : excess humidity is condensed and evacuated towards the outside
- Rubber shock absorbers are incorporated, creating an anti-vibration system
- Wired electronic thermostat regulation
- Washable filter for easy and quick maintenance
- Automatic defrost for maximum cooling efficiency
- 2 year warranty
- This model must be installed by a professionnal


#### **OUTSIDE UNIT**















#### **INSTALLATION DIAGRAM**

With partition walls

Without partition walls







## WINE SP40 The New Generation of Air Conditioners for Wine Cellars

The WineMaster<sup>®</sup> product range was designed to bring optimal air conditioning solutions to the wine cellar of your dreams.

Thanks to constant temperature and humidity preservation, your wines can blossom all year long in a wine cellar under the best conditions, even in the event of extreme outside temperatures  $(-30^{\circ}C to +40^{\circ}C)$ .

This SP40 is available in 3 versions : only the indoor unit differs : ceiling version (CE), wall version (DU) and version suitable for cabinets or small spaces (CA).

REFERENCE	SP40 CA PRO
Air conditioning capacity*	Up to 40 m <sup>3</sup>
Cooling capacity (watt)	900
Heating capacity (watt)	500

CONDENSATION GROUP (EXTERNAL UNIT)	
Airflow rate	840 m³/h
Sound level	42db (1m)
Weight	60 Kg
Dimensions H x W x D	640 x 853 x 424 mm
Electrical supply	230-240 V - 50Hz
Body color	RAL 7012
Coolant	R449 A
Secure pressure switch HP	•
Oil separator	•
Pressure actuated speed controller	•
Waterproof electrical box	•
Check valve	•
Washable air filter	•
Refrigerant line	1/4 and 3/8
Heating belt	•

EVAPORATOR (INSIDE UNIT)	
Weight	17 Kg
Dimensions H x W x D	262 x 517 x 327 mm
Body color	RAL 7012
Number of speeds	2
Dehydrator	•
Thermostatic expansion valve	•
Heating resistor	•
Regulation	wire

<sup>\*</sup> With right insulation and adapted to the volume of the cellar.

\*\* The power could be reduced in function of outside temperature, its why the device may lose capacity to keep the cellar at

12 °C if the outside temperature gets close to 35 °C.


## A STORY OF LOVE AND TERROIR...

It is in the foothills of the Alsatian wineyards, where the wine route starts, that the WineMaster<sup>®</sup> story begins. Our attachment to terroir and our love of wine have always been the source of our thought process and creativity.

Ever since its inception in 1984, the skills and know-how of the men and women of WineMaster<sup>®</sup> have been at the heart of every step in the air conditioner making process.

Quality and detail are what motivate us, and we are proud of our products and their 100 % Alsatian design.

## INNOVATION AND EXCELLENCE ARE WINEMASTER'S KEY VALUES."





Z.I. VIEUX-THANN ■ 18 RUE GUY DE PLACE BP 60010 ■ F68801 THANN CEDEX Tél : +33 (0) 389 377 515 ■ E-mail : contact@winemaster.fr

www.winemaster.fr